



Waterproof Tileable Niche Installation Manual



Manual Contents:

- 1.1P - Necessary Tools and Materials
- 1.2P - Installation of Niche



scan for most current
installation manuals



WWW.UBERTILE.COM

The information pertained within this guide is for reference only and does not supersede instructions from other product manufacturers or building codes.

Always consult and follow manufacturers specific installation and safety instructions BEFORE installing any products.

übertile™ bears no responsibility or liability for damage(s) resulting from the contents contained within this manual.

Information may change without notice. Visit www.ubertile.com for most current revision.

All tasks performed by the product user are at the own risk and liability of the user.



1.1P - Necessary Tools and Materials

Materials required:



Required Materials (not Included)



überseal™
for non-steam shower
applications



Ubertile
Washers



Ubertile
Screws

Tools required: (not included)



300ml Caulking Gun




Utility Knife




Tape Measure



Marker / Pencil



Spirit Level



Power Drill




Flat Spreader

Requirements Backing:

The Ubertile Shower Niche is intended to be installed only AFTER 1/2" Uberboard Waterproof wall panels have been installed. Studs must be 16" on center for the Niche to fit properly with a depth designed for minimum 2x4 studs (3.5" deep)

1.2P - General Requirements & Safety


1



Mark onto the 1/2" UberBoard Wall Panel where your niche is to be installed. The markings must line up to the centre of the 16" O.C. studwork.


TIP: Flip the niche upside down on the wall and trace the perimeter flange of the niche.

2




If necessary, remove screws/washers in the cut path. Carefully cut the UberBoard wall panel and remove the cut-out.

3




Apply Uberseal to the exposed foam edge of the UberBoard wall panel around the entire perimeter of the cutout.

4




Use a minimum of 6 Ubertile Screws and Washers to fasten the niche to the wall.

5



Apply Uberseal to the entire Niche perimeter. Ensure screws are fully covered. While the Uberseal is wet, smooth it flat with the spreader so there is a minimum of 1" overlap of sealant onto both the niche and Uberboard surfaces.



Depending on the model of the Ubertile Niche, it may come with a height adjustable shelf.

To install the shelf:

Apply Uberseal to the back and sides of the shelf, where you want the shelf to sit. Insert shelf into niche at the desired height. Spread out any excess Uberseal so it is smooth.

Wait 24 hours before tiling.