


## Uberboard VAPOR

Tested to ASTM E96 Procedure E, this panels is designed for Steam Shower use.

Part Number	Length	Width	Thickness	pcs / Pallet
205-40072-4	48"	96"	1/2"	48

## Uberboard Vapor Fasteners

Use to fasten Uberboard VAPOR to wood framing.



Part Number	Type	Pack QTY
207-43298-1	<b>Stainless Steel</b> Combo (Screw+Washer)	100



207-42852-2	<b>Stainless Steel</b> Screw only	100
-------------	-----------------------------------	-----



207-42621-0	<b>Stainless Steel</b> Washer only	100
-------------	------------------------------------	-----




**Did you know: Waterproof and Steamproof are not the same thing.**

Some assume that any tile waterproofings can be used in a steam shower. This is false.

Many waterproofing products (including most liquid applied membranes) while waterproof are NOT vapor proof and when used in a steam shower have potential to fail.

Waterproofing used in a steam shower should be tested for vapor permeability using the permeability test ASTM E96 procedure E, at 90% RH.



**Did you know: Steamshower ceilings should be sloped 2" per foot.**

It's obvious a shower floor needs to be sloped to allow water to drain. Whats less obvious is that in a steam shower the ceiling should also be sloped.

Steam rises. As it rises, it eventually loses energy and condensates into liquid water droplets forming on the tiled shower ceiling.

Water droplets on the ceiling require excessive slope to flow towards the wall, and then onward to the sloped shower floor to enter the shower floor drain. For this reason the shower ceiling should be sloped at 2" per foot.

### Uberfabric - 36" width

Use with ISO 13007 C2TES2 modified thinsets in intermittent steam showers.



Part Number	Type	Size	
205-38793-2	36" wide	3' x 82'	246sqft Roll
205-42623-6	36" wide	3' x 36'	108sqft Roll
205-42626-9	36" wide	3' x 10'	30sqft Roll

### Uberfabric - 6" width


Use with ISO 13007 C2TES2 modified thinsets in intermittent steam showers.



Part Number	Type	Size
205-38792-4	6" wide	6" x 82'
205-42622-5	6" wide	6" x 36'
205-43039-3	6" wide	6" x 20'

### Uberfabric- Corners


Use with ISO 13007 C2TES2 modified thinsets in intermittent steam showers.



Part Number	Type	Pack Qty
205-38949-3	Waterproof/Vapor Outside Corner	2pcs
205-38948-0	Waterproof/Vapor Inside Corner	2pcs

### Uberfabric - Penetration Seals

Featuring a flexible coupling to seal to shower hardware penetrations.



Part Number	Type	Pack Qty
205-38947-7	3/4" Pipe Seal	1pcs
205-38950-8	4-1/2" Mixing Valve Seal	1pcs

### High Temperature Silicone

Rated to 400F. For use only around steam pipe



Part Number	Type
202-39423-7	High Temp Silicon

### Foam Backer Rod

Install into grout joints\* prior to silconing to extend silicone life. (\*1/16" - 3/16" wide & 1/4" or deeper)



Part Number	Type	Size
205-41867-1	Foam Backer Rod	35' linear feet