


Uberboard VAPOR

Tested to ASTM E96 Procedure E, this panel is designed for Steam Shower use.

Part Number	Length	Width	Thickness	pcs / Pallet
205-40072-4	48"	96"	1/2"	48

Uberboard Vapor Fasteners

Use to fasten Uberboard VAPOR to wood framing.



Part Number	Material	Type	Pack QTY
207-43298-1	Stainless Steel	Combo (Screw+Washer)	100



207-42852-2	Stainless Steel	Screw only	100
-------------	------------------------	------------	-----



207-42621-0	Stainless Steel	Washer only	100
-------------	------------------------	-------------	-----




Did you know: Waterproof and Steamproof are not the same thing.

It's a common assumption that all waterproofing products can be used in a steam shower. This is false.

Many waterproofing products are NOT designed for steam showers. While waterproof, they are not vapor proof. When the incorrect waterproofing product is used in a steam shower it has the potential to fail.

Waterproofing used in a steam shower should be tested for vapor permeability using the permeability test ASTM E96 procedure E, at 90% RH.



Did you know: Steam shower ceilings should be sloped 2" per foot.

It's obvious that a shower floor needs to be sloped in order to allow water to drain.

What's less obvious is that in a steam shower the ceiling should also be sloped. Steam rises. The steam condensates into liquid water droplets forming on the tiled shower ceiling.

Water droplets on the ceiling require excessive slope to flow towards the wall, and then onward to the sloped shower floor so it can end up at the shower floor drain.

For this reason, the shower ceiling should be sloped at 2" per foot.



Uberfabric - 36" width

Use with IISO 13007 C2TES2 modified thinsets in intermittent steam showers.


Part Number	Type	Size	
205-38793-2	36" wide	3' x 82'	246sqft Roll
205-42623-6	36" wide	3' x 36'	108sqft Roll
205-42626-9	36" wide	3' x 10'	30sqft Roll



Uberfabric - 6" width

Use with IISO 13007 C2TES2 modified thinsets in intermittent steam showers.


Part Number	Type	Size	
205-38792-4	6" wide	6" x 82'	
205-42622-5	6" wide	6" x 36'	
205-43039-3	6" wide	6" x 20'	



Uberfabric- Corners

Use with IISO 13007 C2TES2 modified thinsets in intermittent steam showers.

Part Number	Type	Pack Qty
205-38949-3	Waterproof/Vapor Outside Corner	2pcs
205-38948-0	Waterproof/Vapor Inside Corner	2pcs



Uberfabric - Plumbing Seals

Seals for standard shower plumbing hardware. **Not for use around steam pipe.**

Part Number	Type	Pack Qty
205-38947-7	3/4" Pipe Seal	1pcs
205-38950-8	4-1/2" Mixing Valve Seal	1pcs



High Temperature Silicone

Rated to 400F. **For use ONLY around steam pipe.**

Part Number	Type	
202-39423-7	High Temp Silicone	



Foam Backer Rod

Install into grout joints* prior to siliconing to extend silicone life. (*1/16" - 3/16" wide & 1/4" or deeper)

Part Number	Type	Size
205-41867-1	Backer Rod	35' linear feet